



| Date: 12/2023

MAXIMA MARINE OIL 5 SAE 30

Maxima marine oil 5 SAE 30 is an engine oil developed for marine engines burning residual fuel. It is blended from mineral base oils and especially selected additives, with excellent anti-corrosion and detergent-dispersing properties.

Application

It is used for lubrication of sumps in the slow-speed, two-stroke crosshead diesel engines, with a separate system for cylinders lubrication.

Specifications

API CF

Physical and chemical properties

Characteristic	Unit	Method	Value
Viscosity grade			SAE 30
Viscosity at 100°C	mm ² /s	BAS ISO 3104	11,5-12,5
Viscosity index, min.	-	BAS ISO 2909	90
Density at 15°C	kg/m ³	ASTM D 5002	880
Flash point, min.	°C	BAS ISO 2592	220
Pour point, max.	°C	BAS ISO 3016	-18
TBN, min	mg KOH/g	BAS ISO 3771	5

Note: These characteristics are typical. The manufacturer keeps the right to change characteristics in accordance with these specifications.

Contact: Oil sale department, OPTIMA Group d.o.o. Banja Luka (Sector for development, testing and product quality of Oil refinery Modrica j.s.c. Modrica), telephone: **+387 53 822 359**, email: **primjena@optimagrupa.net**